

M-MV MEDIUM EFFICIENCY V-SHAPED MINI-PLEATED AIR FILTER (LOW PRESSURE DROP)



PRODUCT FEATURES

- V-shape design for low pressure drop
- Mini-pleated design with melt-blown media
- High dust holding capacity with low pressure drop
- Robust construction for stable performance under turbulent airflow
- Available in single-flanged or non-flanged configurations with a fully incinerable polypropylene frame


APPLICATIONS

- Medium efficiency filtration for cleanroom HVAC systems as well as commercial and industrial applications
- Suitable for variable air volume (VAV) HVAC systems
- Ideal for HVAC systems with limited installation space
- Widely used in cleanrooms and other environments with stringent air cleanliness requirements

EFFICIENCY

- M6, F7, F8, F9

PRODUCT STRUCTURE DESCRIPTION



NAME SPECIFICATION

MV - 01 - □□ - □□□ - □□ - □□ - E□ - □□ - 03

- 1 PP
- 2 Enclosure type: X-No flange, D1-Single flange
- 3 Air-tight gasket: E0-None, E1-Upstream, E2-Both sides, E3-Downstream
- 4 Frame material: PL-ABS, SG-Galvanized steel sheet, AL-Aluminium
- 5 Filter: 2-2V, 3-3V, 4-4V, 5-5V
- 6 Dimensions: Width x Height x Depth (WxHxD), unit: mm
- 7 Efficiency: M6, F7, F8, F9
- 8 Manufacturer: MayAir
- 9 Type: Medium efficiency V-Shaped mini-pleated air filter (low pressure drop)

Product Specifications										
Standard Size Medium Efficiency Pressure Drop Parameter Table										
Type	Dimensions W x H x D (mm)	Frame Material	Filter Block (V)	Flange	Airflow (m ³ /h)	Rated Initial Pressure Drop (Pa)				Recommended Final Pressure Drop (Pa)
						M6	F7	F8	F9	
Standard airflow (N)	287 x 592 x 292	ABS/ Galvanized steel/ Aluminium	2	Single	1,700	65	70	75	85	450
	305 x 610 x 292		2	None	1,800	65	70	75	85	450
	592 x 592 x 292		4	Single	3,400	65	70	75	85	450
	610 x 610 x 292		4	None	3600	65	70	75	85	450

Remark:
1. Initial pressure drop performance tolerance is ±15%
2. Special sizes can be provided upon request.

List of Materials	
Frame	ABS / Galvanized steel / Aluminium
Filter Depth	292mm
Filter Material	Melt-blown non-woven fabric
Separator	Hot melt adhesive
Sealant	Polyurethane

Applicable Conditions	
Maximum Temperature	60°C (140°F)